


(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)

PCT

(10) International Publication Number
WO 03/059581 A1

(51) International Patent Classification⁷: **B25J 9/10**,
17/02, 18/06

(21) International Application Number: PCT/SE02/00075

(22) International Filing Date: 16 January 2002 (16.01.2002)

(25) Filing Language: Swedish

(26) Publication Language: English

(71) Applicant (for all designated States except US): **ABB AB**
[SE/SE]; Kopparbergsvägen 2, S-721 83 Västerås (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BROGÅRDH**,
Torgny [SE/SE]; ** (SE). **WÄPPLING**, Daniel [SE/SE];
** (SE). **VALLIN**, Åsa [SE/SE]; Forskarbacken 15:509,
S-104 05 Stockholm (SE). **ANDREASSON**, Mathilda
[SE/SE]; ** (SE). **LUNDBERG**, Ivan [SE/SE]; ** (SE).

(74) Agent: **ABB GROUP SERVICES CENTER AB**; Le-
gal & Compliance/Intellectual Property, S-721 78 Västerås
(SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: INDUSTRIAL ROBOT



(57) Abstract: An industrial robot for moving an object in space comprising a stationary platform, a movable platform arranged for supporting the object, and a first, a second and a third arm to which the platforms are joined. The first arm comprises a first actuator, a first supporting arm influenced by the first actuator and being rotatable around a first axis, and a first linkage. The second arm comprises a second actuator, a second supporting arm influenced by the second actuator and being rotatable around a second axis, and a second linkage. The third arm comprises a third actuator, a third supporting arm influenced by the third actuator and being rotatable around a third axis, and a third linkage. The first and third axes are arranged in parallel and the second supporting arm is freely journaled around a transverse axis that is substantially arranged at right angles to the second axis.

WO 03/059581 A1